

(12) UK Patent Application (19) GB (11) 2 343 107 (13) A

(43) Date of A Publication 03.05.2000

(21) Application No 9921796.0

(22) Date of Filing 16.09.1999

(30) Priority Data

(31) 19850104 (32) 30.10.1998 (33) DE

(71) Applicant(s)

Wessel-Werk GmbH
(Incorporated in the Federal Republic of Germany)
Im Bruch 2, 51589 Reichshof-Wildbergerhütte,
Federal Republic of Germany

(72) Inventor(s)

Horst Dilger
Hans-Joachim Steudtner

(74) Agent and/or Address for Service

Hulse & Co
St James House, 8th Floor, Vicar Lane, SHEFFIELD,
S1 2EX, United Kingdom

(51) INT CL⁷

A47L 9/04

(52) UK CL (Edition R)

A4F FSND

(56) Documents Cited

WO 96/11622 A2


(58) Field of Search

UK CL (Edition Q) A4F FSCB FSND FSSB
INT CL⁶ A47L 9/04 11/18 11/19 11/20 11/204
ONLINE: WPI, EPODOC, PAJ

(54) Abstract Title

Hand activated turbine powered brush nozzle for vacuum cleaner


(57) A vacuum-cleaner nozzle has a housing 1 forming a turbine compartment 3 and a brush compartment 2 and having opening into the turbine compartment an outlet 4 adapted for connection to a fan input and a slot opening 9 into the brush compartment. A brush 8 rotatable in the brush compartment has bristles projecting from the slot. A turbine 6 in the turbine compartment is oriented such that air flow from the slot to the outlet rotates the turbine. A drive or transmission 10 couples the turbine to the brush for rotating the brush when the turbine rotates. A button 12 is displaceable on the housing between an outer position and an inner position and a spring 19 urges the button into the outer position. A link 18 between the button and the drive arrests rotation of the brush on displacement of the button into the outer position. This button is remote from the slot and the housing is formed with a handle 11 adapted to be held by a hand of a user. The button is positioned immediately adjacent the handle for actuation by a finger of the hand on the handle.



At least one drawing originally filed was informal and the print reproduced here is taken from a later filed formal copy.

At least one of these pages has been prepared from an original which was unsuitable for direct photoreproduction.

GB 2 343 107 A



TURBINE-POWERED BRUSH NOZZLE FOR VACUUM CLEANER

SPECIFICATION

FIELD OF THE INVENTION

The present invention relates to a brush nozzle for a vacuum cleaner. More particularly this invention concerns a turbine-powered brush nozzle for such a cleaner.

BACKGROUND OF THE INVENTION

It is known from German patent document 4,036,634 of Fleischer, 4,229,030 of Worwag, 196 14 624 of Dilger, and 197 06 166 of Worwag as well as US patents 4,776,059, 5,249,333, 5,293,665, and 5,920,939 to provide a power nozzle for a vacuum cleaner that has a driven brush serving to raise dirt and dust out of the object being vacuumed. Such a nozzle has a housing forming a turbine compartment and a brush compartment and having opening into the turbine compartment an outlet adapted for connection to a fan input and a slot opening into the brush compartment. The brush is rotatable in the brush compartment and has bristles projecting from the slot. A turbine in the turbine compartment is oriented such that air flow from the slot to the outlet rotates the turbine and some sort of transmission or link

is provided for coupling the turbine to the brush for rotating the brush.

Rather than just having the brush rotating full time, whenever suction is applied to the outlet connection, it is known to provide some sort of element which is actuated to arrest rotation of the brush on displacement of the button into the inner position. This element normally protrudes from the bottom of the nozzle adjacent the slot so that, when the nozzle is pressed against a surface to be power vacuumed, the brush is automatically set in rotation.

The disadvantage of this system is that the brush will operate whenever the nozzle is set down right side up, potentially wearing itself out or wearing a hole in whatever it is left sitting on. Since these nozzles are mainly intended for cleaning floors, such operation is fairly logical, but if the nozzle is to be used on upholstery or drapes this type of operation can cause a problem. In addition if the user does not want to use the power-brushing feature, there is no way to disable it, for instance when vacuuming something delicate like drapes.

OBJECTS OF THE INVENTION

It is therefore an object of the present invention to provide an improved vacuum-cleaner nozzle particularly usable for upholstery and drapes..

Another object is the provision of such an improved vacuum-cleaner nozzle which overcomes the above-given disadvantages.

SUMMARY OF THE INVENTION

A vacuum-cleaner nozzle has according to the invention a housing forming a turbine compartment and a brush compartment and having an outlet opening into the turbine compartment and adapted for connection to a fan input and a slot opening into the brush compartment. A brush rotatable in the brush compartment has bristles projecting from the slot. A turbine in the turbine compartment is oriented such that air flow from the slot to the outlet rotates the turbine. A drive or transmission couples the turbine to the brush for rotating the brush when the turbine rotates. According to the invention a button is displaceable on the housing between an outer position and an inner position and a spring urges the button into the outer position. A link between the button and the drive arrests rotation of the brush on displacement of the button into the outer position. This button is remote from the slot and the housing is formed with a handle

adapted to be held by a hand of a user. The link enables rotation of the brush on displacement of the button into the inner position. The button is positioned immediately adjacent the handle for actuation by a finger of the hand on the handle.

Thus with the system of this invention the user of the nozzle has control of the power-brush feature. Only when he or she actuates the button does the brush rotate. Thus the brush will not rotate when the nozzle is out of use and can even be left off when the nozzle is being used to vacuum something delicate.

The link in accordance with the invention includes a brake engageable with the turbine to arrest same in the inner position of the button. Alternately it includes means for decoupling the turbine from the brush in the inner position of the button.

It is also within the scope of this invention to provide means operated by the link that displace the turbine out of the path of the stream of air being sucked through the housing so that when thus displaced it stops. To this end the turbine is rotationally fixed but axially slidable on a shaft and movable by the button along the shaft between a working position in the stream and a standby position offset therefrom.

BRIEF DESCRIPTION OF THE DRAWING

The above and other objects, features, and advantages will become more readily apparent from the following description, reference being made to the accompanying drawing whose sole figure is a partly diagrammatic vertical section through the nozzle according to the invention.

SPECIFIC DESCRIPTION

As seen in the drawing a nozzle housing 1 forms a brush chamber 2 and a turbine chamber 3 and has an outlet port or connection 4 connected via a hose 5 to the intake of a vacuum-cleaner fan shown schematically at 16. The housing 1 has on its upper wall a standard handle 11 and is formed on its bottom side with an opening or slot 9 through which bristles 20 of a brush 8 rotatable about an axis 8A project.

The turbine chamber 3 holds a turbine 6 rotatable about an axis 6A parallel to the axis 8A and having a plurality of short radially extending vanes 17 oriented such that air passing from the slot 9 to the connection 4 will urge it rotationally in the counterclockwise direction indicated at D. A transmission 10, here constituted as a flat belt, couples the turbine 6 to the roller brush 8 to rotate it so that when suction is applied by the fan 16 a portion of the kinetic energy of the air being

sucked in through the slot 9 can serve to rotate the turbine 6 and brush 8.

According to the invention the turbine 6 has a hub 7 engageable by a spring-loaded double-jaw brake 14 operated through a linkage 18 by a button element 12 urged by a spring 19 into an outer position in which the brake 14 is applied to the drum 7 and inhibits rotation of the turbine 6. A torque spring 21 urges the brake 14 into the closed, rotation-impeding position. Alternately or additionally a roller 15 can be pressed against the transmission belt 10 only when the button 12 is depressed to form a releasable clutch or coupling with the turbine 6 only coupled to the brush 8 when the roller 15 is holding the belt 10 tight. Both systems serve to prevent the brush 8 from rotating unless the button 12, which is easily operated by the same hand that is holding the handle 11, is depressed, by impeding rotation of the turbine 6 with the brake 14 or decoupling the turbine 6 from the roller 8 by detensioning the belt 10 in the illustrated outer position of the button element 12.

This brush nozzle is particularly suitable for use on upholstery or drapes since it allows the user to control the brushing effect which might not be wanted when, for instance, there is the possibility of it catching on and sucking in light fabric or when the covering might be damaged by such brushing action.

WE CLAIM:

1. A vacuum-cleaner nozzle comprising:
 - a housing forming a turbine compartment and a brush compartment and having an outlet opening into the turbine compartment and adapted for connection to a fan input and a slot opening into the brush compartment;
 - a brush rotatable in the brush compartment and having bristles projecting from the slot;
 - a turbine in the turbine compartment and oriented such that air flow from the slot to the outlet rotates the turbine;
 - drive means for coupling the turbine to the brush for rotating the brush;
 - a button displaceable on the housing between an outer position and an inner position;
 - a spring urging the button into the outer position; and
 - link means between the button and the drive means for arresting rotation of the brush on displacement of the button into the outer position and for rotation of the brush by the turbine when the button is in the inner position.
2. The vacuum-cleaner nozzle defined in claim 1 wherein the housing is formed with a handle adapted to be held by a hand of a user, the button being positioned immediately

adjacent the handle for actuation by a finger of the hand on the handle.

3. The vacuum-cleaner nozzle defined in claim 1 wherein the link means includes a brake engageable with the turbine to arrest same in the outer position of the button.

4. The vacuum-cleaner nozzle defined in claim 3 wherein the link means includes means for decoupling the turbine from the brush in the outer position of the button.

5. A vacuum-cleaner nozzle comprising:

a housing forming a turbine compartment and a brush compartment and having an outlet opening into the turbine compartment and adapted for connection to a fan input and a slot opening into the brush compartment;

a handle adapted to be held by a hand of a user on the housing remote from the slot;

a brush rotatable in the brush compartment and having bristles projecting from the slot;

a turbine in the turbine compartment and oriented such that air flow from the slot to the outlet rotates the turbine;

drive means for coupling the turbine to the brush for rotating the brush;

a button displaceable on the housing immediately adjacent the handle between an outer position and an inner position;

a spring urging the button into the outer position; and

link means between the button and the drive means for arresting rotation of the brush on displacement of the button into the outer position and for rotation of the brush by the turbine when the button is in the inner position.



The
Patent
Office



INVESTOR IN PEOPLE

Application No: GB 9921796.0
Claims searched: 1-5

Examiner: Fiona Warner
Date of search: 5 January 2000

Patents Act 1977
Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:

UK Cl (Ed.R): A4F (FSSB, FSND, FSCB)

Int Cl (Ed.7): A47L (9/04, 11/18, 11/19, 11/20, 11/204)

Other: Online: WPI, EPODOC, PAJ

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
A	WO 96/11622 (VORWERK)	

10

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.